

Construction Products Regulations 2011

EC Declaration of Performance

No W 001 CPR 07-2013

WINDOWS WITHOUT RESISTANCE TO FIRE AND/OR SMOKE LEAKAGE CHARACTERISTICS

1. System Identification code: **Profine C70/O70**
2. Type, Batch and/or Serial number: **Esteem/Curve**
3. Intended use: **Domestic and Commercial locations (without resistance to fire and/or smoke leakage characteristics)**
4. Manufacturer:
5. Authorised representative: **Not applicable**
6. Assessment and verification of constancy of performance: **System 3**
7. Relevant Harmonised Standard: **BS EN 14351 - 1:2006 + A1:2010 Annex ZA**

Essential Characteristics	Declared Performance	Test Standard	Test Report Reference & Date
Watertightness	Class 5A (200Pa)	BS EN 1027:2000	KM 561441- BSI 2370/7509986 - 02/02/2012
Dangerous Substances	None	EN 14351-1 2006	Suppliers declarations
Resistance to wind load	Class 3A	BS EN 12211	KM 561441- BSI 2370/7509986 - 02/02/2012
Load bearing capacity of safety devices	Pass	BS EN 948	Exova – 191795- 13/05/2010
Acoustic Performance	NPD	BS EN ISO 140-3	N/A
Thermal Transmittance	1.4 W / (m ² .K)	EN ISO 10077-1&2	KM 566991 BSI – 20/06/2011
Radiation properties	NPD	EN 410	N/A
Air Permeability	Class 3 (600)	BS EN 1026:2000	KM 561441- BSI 2370/7509986 - 02/02/2012

Specific Technical Documentation: **Technical file containing test reports and performance indication reports available by e mailing**

The performance of the product identified in points 1 and 2 is in accordance with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4 and through implementation of **Factory Production Control** in compliance with EN 14351-1:A1:2010.

Signed for and on behalf of the manufacturer by:

Name: Phil Underwood

Position: Managing Director

Date 26th June 2013

