

Construction Products Regulations 2011

EC Declaration of Performance

No W 003 CPR 07-2013

WINDOWS WITHOUT RESISTANCE TO FIRE AND/OR SMOKE LEAKAGE CHARACTERISTICS

1. System Identification code: **Smart Architectural Aluminium Alitherm Profiles 47,300 & 800**
2. Type, Batch and/or Serial number: **ECO 40, 50 & 80**
3. Intended use: **Domestic and Commercial locations (without resistance to fire and/or smoke leakage characteristics)**
4. Manufacturer:
5. Authorised representative: **Not applicable**
6. Assessment and verification of constancy of performance: **System 3**
7. Relevant Harmonised Standard: **BS EN 14351 - 1:2006 + A1:2010 Annex ZA**

Essential Characteristics	Declared Performance	Test Standard	Test Report Reference & Date
Watertightness	Class 7A (300Pa)	BS EN 12208:2000	BRE 0578 - 231960 (20/09/2006); 270707-1 (20/04/2011);
Dangerous Substances	None	EN 14351-1 2006	Suppliers declarations
Resistance to wind load	NPD	BS EN 12210:2000	N/A
Load bearing capacity of safety devices	Pass	BS EN 948	BSI 2370/7999995 – 22/05/2013
Acoustic Performance	NPD	BS EN ISO 140-3	N/A
Thermal Transmittance	1.7 W / (m2.K)	EN ISO 10077-1&2	White Paper Doc L – October 2010
Radiation properties	NPD	EN 410	N/A
Air Permeability	NPD	BS EN 1026:2000	N/A

Specific Technical Documentation: **Technical file containing test reports and performance indication reports available by e mailing**

1. The performance of the product identified in points 1 and 2 is in accordance with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4 and through implementation of **Factory Production Control** in compliance with EN 14351-1:A1:2010.

Signed for and on behalf of the manufacturer by:

Name: Phil Underwood

Position: Managing Director

Date 26th June 2013

